FEATURES:

DEPOSENS[®] 3 controller is the central unit for controlling of DEPOSENS[®] 3 sensors. With this unit sensors can be parameterized, measurement values displayed, saved and optionally forwarded by remote query or Modbus. All operations can be done via touchscreen.

APPLICATION:

Essential for using all kind of DEPOSENS[®] 3 sensors. Recording and forwarding of sensor signals and external signals.

TECHNICAL DATA:

Dimensions: L x W x H: **Enclosure material:** Enclosure rating class: Enclosure color: Data storage: Power supply: Power consumption: Signal inputs:

Signal outputs: Power output: Ambient temperature: Storage temperature: Weight: Mounting:

179 x 199 x 106 mm ABS, PC, CR IP65 Light grey SD-card 230 V AC 50 Hz 50 W 2 x 4-20 mA passive or limit contact 2 x 4-20 mA active 24 V DC 0°C ... 60°C -10°C ... 60°C 1 ka wall brackets / DIN-rail

INSTALLATION:

Install the controller by using the wall brackets or DINrail brackets on a plane vertical surface close to the sensors.

Unplug power supply before (dis)connecting controller and sensors!

ACCESSORIES / OPTIONS:

LAGOTEC

Enclosure color: Protection housing: Remote query: Bus interface:

Anthrazite Steel or ABS LTE-Modem Modbus



POSSIBLE COMBINATIONS:

The controller can operate one or two sensors of any kind.





LAGOTEC GmbH

Niels-Bohr-Str. 43 Wissenschaftshafen D-39106 Magdeburg

lagotec.de contact@lagotec.de T: +49 (0) 391 55 93 460 F: +49 (0) 391 55 93 462